

BLANK PAGE



IS: 7728 - 1984 (Reaffirmed 1995)

Indian Standard SPECIFICATION FOR ANALOGUE DC CURRENT SIGNALS FOR PROCESS CONTROL SYSTEMS

(First Revision)

First Reprint FEBRUARY 1997

UDC 65.011.56.621-523.8 : 621.391.3.024

© Copyright 1984

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG

NEW DELHI 110002

Indian Standard

SPECIFICATION FOR ANALOGUE DC CURRENT SIGNALS FOR PROCESS CONTROL SYSTEMS

(First Revision)

Industrial Process Measurement and Control Sectional Committee, ETDC 67

Chairman

PROF J. K. CHOUDHURY Jadavpur University, Calcutta

Members

Representing

SHRI C. D. AMUDACHARI

SHRI K. P. SARMA (Alternate)

SHRI R. S. ARORA

Project and Development India Ltd, Sindri

Directorate General of Supplies and Disposal New Delhi

SHRI K. R. BANERJEE

Instrumentation Ltd, Kota SHRI K. SURYANARAYANA (Alternate)

SHRI J. S. BHATIA SHRI I. K. CHATTERJEE Electronics Corporation of India Ltd. Hyderabad Durgapur Steel Plant (SAIL), Durgapur

BRIG R. C. DHINGRA

Directorate of Standardization, Ministry of Defence, New Delhi

SHRI M. K. KULSHRESHTA (Alternate) National Test House, Calcutta

SHRI B. P. GHOSH SHRI B. MUKHOPADHYA (Alternate)

SHRI D. P. GOEL

Central Scientific Instruments Organization, Chandigarh

SHRI A. N. AGARWAL (Alternate)

SHRI R. K. GOLIYA Jdeyraj & Sons, Bombay SHRI P. C. GOLIYA (Alternate)

SHRI K. P. GOPALRATNAM

Institute of Design of Electrical Measuring Instruments, Bombay

SHRI P. K. VISWANATHAN (Alternate)

The Calcutta Electric Supply Corporation (India) DR K. DAS GUPTA Ltd. Calcutta

SHRI S. B. MUKHOPADHYAY (Alternate)

Shri S. G. Joshi India Shri T. S. Nagarajan (Alternate) Indian Petrochemicals Corporation Ltd, Vadodara

(Continued on page 2)

© Copyright 1984

BUREAU OF INDIAN STANDARDS

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

Members Representing Institute of Paper Technology, Saharanpur SHRI S. MUKHERJEE SHRI B. C. NAIR MECON, Ranchi SHRI G. BALASUBRAMANIUM (Alternate) SHRI C. B. PANDIT Century Rayon, Kalyan SHRI C. K. CHIMOTI (Alternate) ELECO Pvt Ltd, Hyderabad SHRI D. S. V. RAJU SHRI G. N. MURTHY (Alternate) M. N. Dastur & Co Pvt Ltd, Calcutta SHRI M. N. SARKAR SHRI S. C. Bosk (Alternate) Taylor Instruments Co (India) Ltd. Faridabad SHRI R. D. SHARMA SHRI T. K. ZUTSHI (Alternate) SHRI M. S. SHETTY Tata Consulting Engineers, Bombay SHRI K. G. SRINIVASAN (Alternate) Directorate General of Technical Development, SHRIR. SOUNDHIRARAJAN New Delhi SHRI N. R. SRINIVASAN Indian Oil Corporation Ltd, New Delhi SHRI S. P. MATHURE (Alternate) Department of Atomic Energy, Bombay SHRI CH, SURENDER SHRI S. RAMAKRISHNAN (Alternate) SHRI S. P. SURI National Physical Laboratory (GSIR), New Delhi DR A. F. CHHAPGAR (Alternate) Toshniwal Industries Pvt Ltd, Ajmer SHRI M. G. TOSHNIWAL SHRI S. C. MAHESHWARI (Alternate) All India Instruments Manufacturers and Dealers SHRI VINAY TOSHNIWAL Association, Bombay Siemens India Ltd, Bombay SHRI V. V. VAIDYA SHRI M. M. LOHIA (Alternate) Electronics Commission (IPAG), New Delhi SHRI G. S. VARADAN DR V. P. BHATKAR (Alternate) SHRIK. M. VENKATESAN Mahindra & Mahindra Ltd, 24-Parganas SHRI ARUN MAHINDRA (Alternate) SHRI H. C. VERMA Associated Instruments Manufacturers Pvt Ltd. New Delhi

SHRI M. D. NAIR (Alternate) SHRI A. K. VERMA

Engineers India Ltd, New Delhi

SHRI T. S. NAGESHWARAN (Alternate)

SHRIS. P. SACHDEV, Director General, ISI (Ex-officio Member)

Director (Elec tech)

Secretary

SHRI B. K. MAHATA Deputy Director (Elec tech), ISI

Indian Standard

SPECIFICATION FOR ANALOGUE DC CURRENT SIGNALS FOR PROCESS CONTROL SYSTEMS

(First Revision)

O. FOREWORD

- **0.1** This Indian Standard (First Revision) was adopted by the Indian Standards Institution on 10 August 1984, after the draft finalized by the Industrial Process Measurement and Control Sectional Committee had been approved by the Electrotechnical Division Council.
- **0.2** This standard, first published in 1975, is being revised to bring it in line with the developments at the international level.
- **0.3** The revised standard contains requirements which give specified values for load impedance and power supply voltage. These values were not specified in the earlier standard.
- 0.4 While preparing this standard, assistance has been derived from IEC draft document 65A (Central Office) 8 consolidated revision of IEC Publications 381 (1971) and 381A (1975) 'Analogue direct current signals and process control systems'.
- 0.5 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard applies to analogue dc current signals used in process control systems to transmit information between the elements of systems.

^{*}Rules for rounding off numerical values (revised).

1.2 This standard does not apply to analogue dc current signals entirely used within an element.

2. TERMINOLOGY

- 2.0 For the purpose of this standard, the following definitions shall apply.
- 2.1 Elements of Industrial-Process Measurement and Control Systems Functional units or integrated combinations thereof, which transduce, process or transmit measured values, controlling, controlled and reference variables.
- 2.2 Analogue dc Current Signal A direct current signal, which varies in a continuous manner within its ranges, used in industrial-process measurement and control systems to transmit information.
- 2.3 Range of an Analogue dc Current Signal The range is all values of the signal which lie between defined limits.
- 2.4 Lower Limit The specified lowest value of the range.

Note — The lower limit may be either zero or a finite value. When zero is used, this is called 'true zero'; when a finite value is used, this is called 'live zero'.

- 2.5 Upper Limit The specified highest value of the range.
- 2.6 Load Impedance The resultant of the impedances of all connected receiving elements and connecting lines within the signal circuit.
- 2.7 Ripple Content of the dc Signal The ratio of the peak-to-peak value of the alternating component with respect to the analogue dc current signal range.
- 2.8 Signal Circuit Common Bus A number of signal circuits may have a common direct electrical connection. This is the signal circuit common bus, which may, or may not, be connected to earth.
- 2.9 Power Supply The supply which enables a system element to generate direct current signals by supplying the necessary dc power.
- 2.10 Ripple Content of the Nominal Power Supply Voltage The ratio of the peak-to-peak value of the alternating component with respect to the nominal power supply voltage.

3. SPECIFIED VALUES

3.1 Ranges of Analogue dc Current Signals — The ranges of analogue dc current signals shall be as given in Table 1.

TABLE 1 RANGES OF ANALOGUE dc CURRENT SIGNALS (Clause 3.1)

LOWER LIMIT MA	UPPER LIMIT mA
4	20
0	20

Note 1 — 4 to 20 mA range is the preferred range.

Note 2 - 0 to 20 mA range is the non-preferred range.

- 3.2 Out of Range Values of Analogue dc Current Signals In the case of the preferred range the 0 mA-value is exclusively reserved for indication of a signal circuit or power supply failure. In case of both preferred and non-preferred ranges, the maximum current shall be limited to 20 mA.
- 3.3 Ripple Content of the dc Current Signal The ripple content of the signal shall not exceed 0.25 percent of the upper limit if the information is carried by the mean value of the signal. If the information is carried by the instantaneous value of the signal, the ripple content shall be specified for the element.
- 3.4 Signal Common The point in the signal circuit with the lowest potential shall be the signal common. If the signal common is connected to the power supply, it shall be connected to the power supply negative terminal (or zero volt terminal in case of a bipolar power supply).
- 3.5 Earthing If a signal circuit or power supply is to be earthed, the bus with low potential shall be earthed.
- 3.6 Load Impedance A transmitting or control system element shall be capable of continuously driving any load between 0 and 600 ohms.
- 3.7 Power Supplies Any transmitting system element using a power supply external to it shall be capable of operating with a power supply voltage which can vary between 18 V dc and 30 dc.

The ripple content of the power supply shall not exceed 2 percent peak-to-peak of the nominal value. The use of stabilized power supplies is possible.

For evaluation and comparison of systems element characteristics a reference power supply voltage of 24 V dc is recommended.

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones: 323 0131, 323 3375, 323 9402

Fax: 91 11 3234062, 91 11 3239399, 91 11 3239382

Telegrams: Manaksanstha

(Commo	n to all Offices)	
Central Laboratory:	Telephone	
Plot No. 20/9, Site IV, Sahibabad Industrial Area, SAHIBABAD 201010	8-77 00 32	
Regional Offices:		
Central: Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002		
*Eastern: 1/14 CIT Scheme VII M, V.I.P. Road, Maniktola, CALCUTTA 7000	54 337 86 62	
Northern: SCO 335-336, Sector 34-A, CHANDIGARH 160022	60 38 43	
Southern: C.I.T. Campus, IV Cross Road, CHENNAI 600113	235 23 15	
†Western : Manakalaya, E9 Behind Marol Telephone Exchange, Andheri (Ea: MUMBAI 400093	st), 832 92 95	
Branch Offices:		
'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD 380001	550 13 48	
‡Peenya Industrial Area, 1st Stage, Bangalore-Tumkur Road, BANGALORE 560058	839 49 55	
Gangotri Complex, 5th Floor, Bhadbhada Road, T. T. Nagar, BHOPAL 46200	3 55 40 21	
Plot No. 62-63, Unit VI, Ganga Nagar, BHUBANESHWAR 751001	40 36 27	
Kalaikathir Buildings, 670 Avinashi Road, COIMBATORE 641037	21 01 41	
Plot No. 43, Sector 16 A, Mathura Road, FARIDABAD 121001	8-28 88 01	
Savitri Complex, 116 G. T. Road, GHAZIABAD 201001	8-71 19 96	
53/5 Ward No. 29, R. G. Barua Road, 5th By-lane, GUWAHATI 781003	54 11 37	
5-8-58C, L. N. Gupta Marg, Nampally Station Road, HYDERABAD 500001	20 10 83	
E-52, Chitaranjan Marg, C-Scheme, JAIPUR 302001	37 29 25	
117/418 B, Sarvodaya Nagar, KANPUR 208005	21 68 76	
Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval Kishore Road, LUCKNOW 226001	23 89 23	
Patliputra Industrial Estate, PATNA 800013	26 23 05	
T. C. No. 14/1421, University P. O. Palayam, THIRUVANANTHAPURAM 695034	6 21 17	
NIT Building, Second Floor, Gokulpat Market, NAGPUR 440010	52 51 71	
Institution of Engineers (India) Building, 1332 Shivaji Nagar, PUNE 411005	32 36 35	
*Sales Office is at 5 Chowringhee Approach, P. O. Princep Street,	07.40.05	
CALCUTTA 700072	27 10 85	
†Sales Office is at Novelty Chambers, Grant Road, MUMBAI 400007	309 65 28	
‡Sales Office is at 'F' Block, Unity Building, Narashimaraja Square, BANGALORE 560002	222 39 71	